

## Style 3259-1-SS **premium** TECHNICAL DATA

<b>Base Fabric</b>		<b>Tolerance</b>	<b>Test Methods</b>
<b>Yarn</b>			DIN 53830-3
Warp	EC9 136 tex	± 5%	
Weft	EC9 136 tex	± 5%	
<b>Thread Count</b>			DIN EN 1049-2
Warp	18,0 1/cm	± 5%	
Weft	13,0 1/cm	± 5%	
<b>Weight</b>	430 g/m <sup>2</sup>	± 5%	DIN EN 12127
<b>Weave</b>	Cross Twill		ISO 9354
<b>Temperature Resistance</b>	550°C		

<b>Coated Fabric</b>	<b>Tolerance</b>	<b>Test Methods</b>
<b>Coating:</b>	coated with high temperature flame retardant silver-grey silicone rubber on one side	
	-provides excellent abrasion – Resistant from: UV/water/fluids-acids	
<b>Weight</b>	510 g/m <sup>2</sup>	± 10% DIN EN 12127
<b>Thickness</b>	0,40 mm	± 10% DIN EN ISO 5084
<b>Tensile Strength</b>		DIN EN ISO 13934-1
Warp	> 5.300 N/5cm	
Weft	> 3.300 N/5cm	
<b>Temperature Resistance</b>	250°C c	

